

Samsung Warming Drawer WS200/300

[> Web link](#)

Model
Samsung Warming Drawer WS200/300

Manufacturer ID
NL20T8100WK/UR

Article no.
500.000.110.00

Appliance type
Warming drawers

Construction
Euro Norm 60 cm

VRG
7.51

Price CHF
957.- excl. VAT

Highlights

- Capacity: tableware for 6 or 20 plates at Ø 28 cm each
- Front without handle - opens with light tapping
- Non-slip mat
- Heating evenly
- Telescope rails
- Temperature continuously variable from 30°C to 80°C
- Load-bearing capacity up to 25 kg
- Keeping food warm
- LED status indication

Product description

Construction: **Euro-Norm 60 cm**
GTIN-Nr.: **8806090119354**

Consumption**Energy consumption**

Keeping warm: **420 W**

Energy consumption: **420 W**

Design

Color: **Onyx black brilliant**

Material: **Glass**

Frame / material: -

Display and operation

Display and lighting: **LED status indicator, orange**

Operation: **Rotary knob (mechanical)**

Performance properties

Adjustable temperature: **30°C - 80°C**

Increase: **5°C**

Interior capacity: **25,2 L**

Dimensions

Height: **14 cm**

Width: **59.5 cm**

Unit dimensions (H x W x D): **140 x 595 x 574 mm**

Empty weight

Unit weight: **16.3 kg**

Fittings

Interior: **Stainless steel**

Bottom: **Non-slip mat**

Drawer: **Telescope rails**

Capacity: **25.2 L**

Number of shelf levels: **1**

Lighting / inspection window: **- / -**

Telescope rails: **Yes**

Load-bearing capacity: **up to 25 kg**

Functions

Defrosting: **30°C**

Letting dough rise: **40°C bis 50°C**

Pre-warming cups: **40°C bis 50°C**

Pre-warming plates: **60°C bis 70°C**

Keeping food warm:

Samsung Warming Drawer WS200/300[> Web link](#)**80°C****Loading**Espresso cups: **max. 80 pcs**Plates (28 cm): **max. 20 pcs****Electrical connection**Supply voltage: **230 V**Frequency: **50 Hz**Connection value: **0.42 kWh**Fuse protection: **10 A**Length power connection: **1.5 m**Power plug: **plug CH adapter type 12, 10 A****Technische Daten**Standard width: **Euro-Norm 60 cm**Niche height: **min. 142 mm**Niche width: **560 - max. 568 mm**Niche depth: **min. 550 mm**Unit width in mm: **595 mm**Unit height in mm: **140 mm**Unit depth in mm: **574 mm****Packaging**Weight, incl. packaging: **18.3 kg**Packaging dimensions (H x W x D): **250 x 670 x 650 mm**