

BORA GP4U > Web link



Brief description Induction cooktop with extraction system Mode of operation Recirculated air

Article no. 40.002.246.00

VRG 10.00 Price CHF 2180.- O excl. VAT

Product description

BORA induction cooktop with integrated cooktop extractor (Recirculation) GP4U

Technical data

Supply voltage

400 V 2N / 3N 230 V

Frequency

50 Hz

Max. power consumption

7.6 kW (4.4 kW)

Fuse / mains supply

3 x 16 A, 2 x 16 A, 1 x 32 A

Dimensions (excluding duct connections)

760 x 515 x 196 mm

Weight (including accessories/packaging)

Surface material

SCHOTT CERAN® SURFACE MATERIAL

Cooking zone Hyper 1 radiant hob front left 2300 W ø 210 mm Power level 3000 W Cooking zone 1 rear radiant hob 1400 W ø 175 mm Power setting 1 - 9, P

Extraction system

Maximum air volume

624 m3/h

Power setting

1, 2, power level

Recirculation connection

650 x 90 mm

Air circulation filter

Filter media

Activated carbon with ion exchange

Service life

max. 150 h, 1 year

Planning tip

Please provide good ventilation under the hob

Please note that for induction hobs, cookware suitable for induction must be used.

Scope of delivery:

Ceramic induction hob with extraction device (Recirculation air) GP4U

Inlet nozzle GP4ED

Grease filter brushed stainless steel

Activated carbon filter set BAKFS

Flexible duct with fixing screws

Mounting tabs

Sealing strip

Clips for cable fixing

Set of height compensation discs

Operating and installation instructions

Connecting cable 15 m



BORA GP4U > Web link

Product description:

Cooktop:

Power level for both front cooking zones Automatic switch-off Timer function Residual heat indicator Pot detection Child lock

Vacuum system:

Power adjustment by touch control Timer switch-off Automatic switch-off Filter maintenance indicator Power level Mains socket on the front

Other Articles

You can find additional articles here > Weblink



40.002.246.00 / CHF 2180.-BORA GP4U