

> Web link

BORA X Pure PUXU2

Brief descriptionVRSurface induction glass ceramic cooktop with extraction
system (shiny glass ceramic)VRMode of operation5.5Recirculated airPriArticle no.37540.002.956.00375

VRG 5.56 Price CHF 3759.- O excl. VAT

Product description

BORA surface induction cooktop with integrated cooktop extractor (recirculated air) PUXU2

Product description

Cooktop

- Shiny glass ceramicPower level for each cooking zone
- Bridge function
- Timer cooking zones
- Short-term alarm clock
- Residual heat display
- Pot detection
- Pause function
- Warming function
- Parental lock
- Safety shutdown
- Demo mode
- Extraction system
- Three-colour sControl+ operation
- Power stage
- Automatic trigger control
- Automatic overrunning
- Cleaning lock
- Filter service indicator
- Front power socket

Scope of delivery

- Surface induction hob with integrated hob extractor recirculated air PUXU2
- PUXED2 inlet nozzle, black
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAKF
- Operating and intallation instructions
- Drilling template
- Mounting clamps, sealing tape
- Height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

Planning guidelines

- Ensure adequate ventilation under the hob
- Please note that induction-compatible cookware must be used for induction hobs
- Connection cable must be provided by the customer
- Front power socket
- Telescopic pull-out (pull-out up to 80 mm) of the air cleaning box for connection to the rear wall of the carcase.
- For extra-deep cooktop base units, the telescopic pull-out can be extended by 105 mm with the additional PULBTA telescopic pull-out (available as an accessory).

Technical data

Supply voltage 400 V 2N /3N 230 V

Frequency 50 Hz

Maximum power consumption 7,6 kW

Fuse protection / power connection 3 x 16 A

BORA X Pure PUXU2

2 x 16 A

Equipment mass (without duct connections) 830 x 515 x 199 mm

Weight (incl. accessories / packaging) 24,5 kg

Material surface Glass Ceramic

Cooktop

Induction cooking zone front 230 x 230 mm 2100 W

Power level 3000 W

Induction cooking zone rear 230 x 230 mm 2100 W

Power level 3000 W

Power levels 1-9, P

Trigger system

Power levels 1 - 9, P

Connection on exhaust air side 445 × 137 mm

Recirculation filter

Filter medium Activated carbon with ion exchanger

Material Filter panel with fine filter

Service life max. 150 h / 1 year

Not compatible with PUED inlet nozzle

Other Articles



40.002.958.00 / CHF 3985.-BORA X Pure Rough PUXU2R



40.002.390.00 / CHF 2290.-BORA S Pure PURSU



40.002.955.00 / CHF 3593.-BORA X Pure PUXA2



40.002.759.00 / CHF 3068.-BORA M Pure PURMA



40.002.956.00 / CHF 3759.-BORA X Pure PUXU2



40.002.760.00 / CHF 3234.-BORA M Pure PURMU



40.002.065.00 / CHF 2713.-BORA Pure PURA



40.002.066.00 / CHF 2879.-BORA Pure PURU



You can find additional articles here > Weblink

40.002.413.00 / CHF 2124.-BORA S Pure PURSA

> Web link

SUTER

Prices excl. VAT / product details are based on the date the list was generated, up-to-date information is available online.