

**BORA X Pure Rough PUXU2R**
[> Web link](#)


**Article no.**  
40.002.958.00

**VRG**  
5.56  
**Price CHF**  
3985.- O excl. VAT

**Product description**
**BORA surface induction cooktop with integrated cooktop extractor (recirculated air) PUXU2R**
**Product description**
**Cooktop**

- Matt glass ceramic
- Power level for each cooking zone
- Bridge function
- Timer cooking zones
- Short-term alarm clock
- Residual heat display
- Pot detection
- Pause function
- Warming function
- Parental lock
- Safety shutdown
- Demo mode

**Extraction system**

- Three-colour sControl+ operation
- Power stage
- Automatic trigger control
- Automatic overrunning
- Cleaning lock
- Filter service indicator
- Front power socket

**Scope of delivery**

- Surface induction hob with integrated hob extractor - recirculated air PUXU2R
- PUXED2 inlet nozzle, black
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAKF
- Operating and installation instructions
- Drilling template
- Mounting clamps, sealing tape
- Height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

**Planning guidelines**

- Ensure adequate ventilation under the hob
- Please note that induction-compatible cookware must be used for induction hobs
- Connection cable must be provided by the customer
- Front power socket
- Telescopic pull-out (pull-out up to 80 mm) of the air cleaning box for connection to the rear wall of the carcass.
- For extra-deep cooktop base units, the telescopic pull-out can be extended by 105 mm with the additional PULBTA telescopic pull-out (available as an accessory).

**Technical data**
**Supply voltage**

400 V 2N /3N  
230 V

**Frequency**

50 Hz

**Maximum power consumption**

7,6 kW

**Fuse protection / power connection**

3 x 16 A

**BORA X Pure Rough PUXU2R**[> Web link](#)

2 x 16 A

**Equipment mass (without duct connections)**

830 x 515 x 199 mm

**Weight (incl. accessories / packaging)**

24,5 kg

**Material surface**

Glass Ceramic

**Cooktop****Induction cooking zone front**

230 x 230 mm

2100 W

**Power level**

3000 W

**Induction cooking zone rear**

230 x 230 mm

2100 W

**Power level**

3000 W

**Power levels**

1-9, P

**Trigger system****Power levels**

1 - 9, P

**Connection on exhaust air side**

445 x 137 mm

**Recirculation filter****Filter medium**

Activated carbon with ion exchanger

**Material**

Filter panel with fine filter

**Service life max.**

150 h / 1 year

Not compatible with PUED inlet nozzle