

BORA GP4U

[> Web link](#)

Article no.
40.002.246.00

VRG
10.00
Price CHF
2180.- O excl. VAT

Product description

BORA induction cooktop with integrated cooktop extractor (Recirculation) GP4U

Technical data

Supply voltage

400 V 2N / 3N
230 V

Frequency

50 Hz

Max. power consumption

7.6 kW (4.4 kW)

Fuse / mains supply

3 x 16 A, 2 x 16 A, 1 x 32 A

Dimensions (excluding duct connections)

760 x 515 x 196 mm

Weight (including accessories/packaging)

25 kg

Surface material

SCHOTT CERAN® SURFACE MATERIAL

Hob

Cooking zone Hyper 1 radiant hob front left
2300 W ø 210 mm

Power level

3000 W

Cooking zone 1 rear radiant hob

1400 W ø 175 mm

Power setting

1 - 9, P

Extraction system

Maximum air volume

624 m³/h

Power setting

1, 2, power level

Recirculation connection

650 x 90 mm

Air circulation filter

Filter media

Activated carbon with ion exchange

Service life

max. 150 h, 1 year

Planning tip

Please provide good ventilation under the hob

Please note that for induction hobs, cookware suitable for induction must be used.

Scope of delivery:

Ceramic induction hob with extraction device (Recirculation air) GP4U

Inlet nozzle GP4ED

Grease filter brushed stainless steel

Activated carbon filter set BAKFS

Flexible duct with fixing screws

Mounting tabs

Sealing strip

Clips for cable fixing

Set of height compensation discs

Operating and installation instructions

Connecting cable 15 m

Product description:**Cooktop:**

Power level for both front cooking zones
Automatic switch-off
Timer function
Residual heat indicator
Pot detection
Child lock

Vacuum system:

Power adjustment by touch control
Timer switch-off
Automatic switch-off
Filter maintenance indicator
Power level
Mains socket on the front