SUTER

BORA PKIW3 Induction Glass Ceramic Wok, Professional 3.0

> Web link



Article no. 40.002.240.00 VRG 2.31 Price CHF 2767.- O excl. VAT

Product description

Product description BORA Professional 3.0 Induction glass ceramic wok PKIW3

Power level Residual heat indicator Pause function Configuration menu Cooking zone display on control knob Demo mode Pot detection Automatic boil-on function Digital power level display on the control knob Child safety lock Safety shut-off

Technical data

Supply voltage 220 - 240 V Frequency 50 Hz Maximum power consumption 3.0 kW Maximum connected load 3.0 kW Fuse protection at least 1 x 16 A Power levels 1-9, P Weight (incl. accessories / packaging) 9.5 kg Surface material SCHOTT CERAN Mains cable 1.5 m Dimensions (width x depth x height) 370 x 540 x 128 mm Cooking zone size Ø 310 mm Cooking zone power 2400 W Cooking zone power level 3000 W

Scope of delivery:

Induction glass ceramic wok PKIW3 2 x control knobs Mounting lugs Height compensation plate set Operating and assembly instructions 2 x Connecting cable for operating toggle Connecting cable to fume cupboard Mains cable (L, N, PE), without plug

Planning information:

Due to the overall height of 128 mm, the appliance cannot be installed above the exhaust air duct. Ensure sufficient ventilation below the induction hob. Wok pan diameter 310 mm Use a wok which loses its magnetic properties as the temperature rises (overheating protection). We recommend using the wok pan we offer.

SUTER

BORA PKIW3 Induction Glass Ceramic Wok, Professional 3.0

> Web link

Accessory

Optional accessories



> Weblink 40.001.349.00 / CHF 424.-Induction wok pan HIW1



> Weblink 40.002.167.00 / CHF 176.-Flat lid for wok pan HIW1



> Weblink 40.001.767.00 / CHF 97.-BORA socket USTJ



> Weblink 40.002.034.00 / CHF 135.-BORA socket USTJAB All Black



> Weblink
 40.001.775.00 / CHF 19. BORA Glass ceramic
 scraper UGS

Compatible Articles



> Weblink 40.002.243.00 / CHF 74.-BORA Lock collar PKR3 Prof. 3.0





> Weblink 40.002.244.00 / CHF 111.-BORA Lock collar PKR3AB Prof. 3.0

PKIW3

BORA Pro induction wok cooktop









technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.0 kW
Maximum power rating	3.0 kW
Minimum fuse protection	1 x 16 A
Power supply cable length	1,5 m
Dimensions (width x depth x height)	370 x 540 x 128 mm
Weight (incl. accessories/packaging)	9.5 kg
Surface material	SCHOTT CERAN®
Cooktop power levels	1 – 9, P
Size of cooking zone	Ø 310 mm
Cooking zone output	2400 W
Cooking zone power setting output	3000 W





Product description

- · Intuitive control knob • Variable heat retention function
- childproofing feature
 Cooking zone timers
- Timer
- Pause function
- automatic heat up function
- Increased resistance against breakage
- Modular system
 Demo mode

- Scope of delivery Induction wok cooktop PKIW3
- 2 x control knobs
- 2 x connection cables for the control knobs
- · Connection cable to the extractor
- · operating and installation instructions
- · height adjustment plate set • mounting straps

Accessories

HIW1 induction wok, Controlinduc[®], stainless steel, Ø 360 mm

- product- and planning instructions
 The installation height of 128 mm means that the device cannot be installed over the exhaust ducting
 Ensure sufficient ventilation of the area below the cooktop.
 Glass ceramic mould Diameter 310 mm
 Use a wok that loses its magnetic properties when the temperature rises (overheating protection) We recommend using the BOPA induction wok

- (overheating protection). We recommend using the BORA induction wok.