

BORA ULS base fan

[> Web link](#)

Article no.
40.002.251.00

VRG
0.56

Price CHF
1453.- O excl. VAT

Product description

Technical data

Supply voltage: 230 V
 Frequency: 50 Hz
 Power consumption: 170 W
 Maximum current consumption: 1.4 A
 Maximum ambient temperature: 40 °C
 Maximum flow rate: 750 m³ / h
 Maximum static pressure: 587 Pa
 Weight (incl. packaging): 2.85 kg
 Dimensions (width x depth x height): 370 x 388 x 100 mm
 Material of housing: Plastic
 Connection cable: 0.6 m
 Connection on exhaust side: BORA Ecotube, 245 x 89 mm

Product description

for horizontal installation in the plinth area, in the floor structure or suspended from the cellar ceiling
 highest energy efficiency class and low energy consumption (EC technology)
 integrated fixing points for ceiling mounting
 Sound and vibration decoupling
 removable inlet spigot for plinth heights of 100 mm and more
 The fan is designed for use with the BORA hob extractors PKA3 and CKA2
 In the case of an exhaust air path longer than 6 m or high pressure losses, the plinth fan must be supplemented with another BORA fan module.

Scope of delivery

BORA plinth fan ULS
 Installation instructions

Planning information

For suspended installation, a drill hole diameter of Ø 180 mm must be provided for the ceiling opening.
 With these units, the duct connection is designed for the BORA Ecotube duct system. To connect BORA Ecotube (connection 245 x 89 mm) with Naber connections (222 x 89 mm), an adapter (EFA, 40.001.779) is available / can be ordered separately.

Accessory

Optional accessories



[> Weblink](#)

40.001.599.00 / CHF 75.-
 BORA mains cable EC
 10 m



[> Weblink](#)

40.001.600.00 / CHF 62.-
 BORA control line EC 10
 m