

BORA X Pure PUXU2
[> Web link](#)


Article no.
40.002.956.00

VRG
5.56
Price CHF
3759.- O excl. VAT

Product description
BORA surface induction cooktop with integrated cooktop extractor (recirculated air) PUXU2
Product description
Cooktop

- Shiny glass ceramic
- Power level for each cooking zone
- Bridge function
- Timer cooking zones
- Short-term alarm clock
- Residual heat display
- Pot detection
- Pause function
- Warming function
- Parental lock
- Safety shutdown
- Demo mode

Extraction system

- Three-colour sControl+ operation
- Power stage
- Automatic trigger control
- Automatic overrunning
- Cleaning lock
- Filter service indicator
- Front power socket

Scope of delivery

- Surface induction hob with integrated hob extractor - recirculated air PUXU2
- PUXED2 inlet nozzle, black
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAKF
- Operating and installation instructions
- Drilling template
- Mounting clamps, sealing tape
- Height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

Planning guidelines

- Ensure adequate ventilation under the hob
- Please note that induction-compatible cookware must be used for induction hobs
- Connection cable must be provided by the customer
- Front power socket
- Telescopic pull-out (pull-out up to 80 mm) of the air cleaning box for connection to the rear wall of the carcass.
- For extra-deep cooktop base units, the telescopic pull-out can be extended by 105 mm with the additional PULBTA telescopic pull-out (available as an accessory).

Technical data
Supply voltage

400 V 2N / 3N
230 V

Frequency

50 Hz

Maximum power consumption

7,6 kW

Fuse protection / power connection

3 x 16 A

BORA X Pure PUXU2

[> Web link](#)

2 x 16 A

Equipment mass (without duct connections)

830 x 515 x 199 mm

Weight (incl. accessories / packaging)

24,5 kg

Material surface

Glass Ceramic

Cooktop**Induction cooking zone front**

230 x 230 mm

2100 W

Power level

3000 W

Induction cooking zone rear

230 x 230 mm

2100 W

Power level

3000 W

Power levels

1-9, P

Trigger system**Power levels**

1 - 9, P

Connection on exhaust air side

445 x 137 mm

Recirculation filter**Filter medium**

Activated carbon with ion exchanger

Material

Filter panel with fine filter

Service life max.

150 h / 1 year

Not compatible with PUED inlet nozzle